

KÖSTER

KSK Primer BL

Technical guideline / Article number **7.32**
Issued: 1st of November 2005 Draft

Solvent free, strongly adhesive primer for KSK-membranes on polymer-modified bitumen basis

Features

KÖSTER KSK Primer BL is a solvent free, strongly adhesive, thin fluid primer for KSK-membranes on the basis of bitumen with a high polymer content. It is characterized by very good adhesion to dry and moist mineral substrates.

Storage

Store the material in a cool but frost free place; in originally sealed packages, it can be stored for 12 months.

Technical guidelines cited

KÖSTER Bikuplan® KSK membranes

Art. No. 10.311 – 10.361

Technical data

Solid particle content	> 55 %
Minimum application temperature	+ 5 °C
Curing time (at 20 °C)	24 hours
Application of next layer (at 20 °C)	approx. 3 – 4 hours
(at 10 °C)	approx. 5 – 7 hours

Field of application

KÖSTER KSK Primer BL is a primer for bonding KÖSTER Bikuplan® KSK membranes.

Application

KÖSTER KSK Primer BL is applied thoroughly undiluted in one coat by roll or brush or by spraying it on.

Consumption

250 - 400 g / m² per coat (in case of strongly absorbent substrates, two coats are necessary – total consumption approx. 500 g / m²)

Cleaning of tools

Clean tools immediately after use with clean water.

Packaging

15 l canister

The accurate and thereby effective and successful application of our products is not subject to our control. The guarantee can therefore only be applied to the quality of our products within the scope of our terms and conditions, not, however, for their effective and successful application. These guidelines replace all previous ones.