



KÖSTER Caulking Gun

For standard 310 ml cartridges, e. g. KÖSTER KB Flex 200 and KÖSTER Crisin 76 Cream.

Features

The KÖSTER Caulking Gun is a robust and reliable hand injection pump for installing 310 ml / 500 g KÖSTER KB-Flex 200 cartridges and 310 ml / KÖSTER Crisin Cream cartridges.

KÖSTER Spatula

Prod. code X 987 001

Technical Data

Mechanical thrust ratio	12:1
Distance per Stroke	7 mm
Maximum force	2.5 kN
Carriage Length	239 mm (9.42 in)
Cartridge capacity	310ml (10.5oz)
Weight	0.79kgs (1.74lbs)

Fields of Application

For more information see the Technical Guidelines for KÖSTER KB-Flex 200 and KÖSTER Crisin Cream

Advantages:

- Patented adjustable screw to cut thrust gaps
- Dripleless design
- Suitable for Low and Medium viscosity materials
- Patented wave spacer makes rotated carriage stably and smoothly

Product Description:

- Aluminum alloy handle / Steel trigger
- Twin heat treatment steel push plates
- Steel zinc plated push rod
- Patented 360° Rotary type of steel riveted carriage
- 1.5mm steel zinc plated push piston
- Built-in cartridge puncture tool
- Ladder hook puller
- Dripleless design
- Packing: 1 pce/ PE bag, 12pcs/ carton

Cleaning

After use clean the KÖSTER Special Caulking Gun, tools and any residues with a cloth or paper towels, oily residue can be removed with KÖSTER Universal Cleaner.

Packaging

J 989 001 piece

Storage

When stored clean and dry there is no limited storage time.

Safety

Observe all Local, State, and Governmental safety requirements when using tools of all types.

Related products

KÖSTER Cleaning Brush	Prod. code IN 959 001
KÖSTER KB-Flex 200	Prod. code J 250
KÖSTER Crisin Cream	Prod. code M 278

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.